
Page 1 of 1

6 Volt, 15 Watt Unit Suitable for Wet Locations and Corrosive Environments

The WE4X series is a wet location, corrosive environment resistant emergency unit.



Complete Fixture consists of base unit with lamps.

How to Specify:



WE4X = 6V, 15W Wet Location Unit

Features

- 1. Illumination: Illumination is accomplished with two adjustable lamp heads with 6 VDC, 7.2W Par 36 style lamps.
- 2. Housing: Constructed of fiberglass, corrosion-resistant, grey housing.
- 3. Electronics: 120/277 VAC dual voltage input with solid-state circuitry. Charging system is complete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp and test switch.
- 4. Battery: Maintenance free, sealed lead calcium battery has an estimated service life of 5 years, and an operating temperature range of 65°F (19°C) to 85°F (30°C).
- 5. Warranty: Electronics: 3 years; Battery: 1 year full, 4 years pro-rata

Code Compliance

UL 924 listed for wet locations.

National Electrical Code (NEC), NFPA70 and NFPA101 life safety codes; and OSHA safety code illumination standards.

Job Information	Туре:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • B0308

